



EAST PENN DEKA INTIMIDATOR

9A34

ADVANCED LIFE, POWER AND DURABILITY (A3)

MAINTENANCE FREE – AGM VALVE REGULATED

MARINE

- BCI Group 34, 12V
- CCA 775 / CA 955
- Reserve Capacity [min]: 120@25 A
- Reserve Capacity [Ah@20hr rate]: 55
- Weight: 43 lbs.
- Length- 10 ³/₄ in (273 mm)
- Width- 6 \(\frac{7}{8} \) in (175 mm)
- Height- 8 in (203 mm)
- Terminal Positive on LEFT

QUALITY SYSTEM
ISO 9001
ISO/TS 16949

ISO 9001 QS 9000 WIRE & CABLE DIVISION: ISO 14001 QUALITY SYSTEM CERTIFIED TO 150 9001 QS 9000

SOLAR



Conventional automotive batteries can be extremely intimidated by the power demands of today's vehicles - falling short of delivering critical dependability and performance. Cars, trucks, SUVs, and other passenger vehicles have more electronics than ever before.

Intimidator automotive batteries are especially designed to handle factory installed electronics to anything that plugs in or turns on, and still deliver dependable starting power. With almost 2x the endurance* in severe service and 2x the cycle life*, these batteries are equipped for the toughest conditions and the most intense electrical power demands.

Intimidator automotive batteries are also ideal for tuner cars or off-road vehicles, offering superior power for high-performance equipment and a high-impact design for rugged, back road adventures.








INTIMIDATOR® AGM Series for AUTOMOTIVE HEAVY DUTY APPLICATION

- Over 2x the cycle life* maximizes accessory and trolling power
- 20x more vibration resistant* for wave-pounding protection
- Best all-purpose service provides starting, cycling, and deep cycle capability
- Safer install and transport with no-spill design to prevent leaking acid
- High freeze-resistance provides better all weather performance
- Better capacity protection during periods of infrequent use

*above and beyond conventional designs





INTIMIDATOR **AGM** Enhanced Electrolyte Suspension

System

SHOCK-ABSORBING SEPARATORS resist vibration and damage.

ENHANCED DURABILITY **DESIGNS** withstand wear of extended cycling service

SUPERIOR ELECTROLYTE **RETENTION** prevents dry out and acid leaks.

LOWER CURRENT RESISTANT SEPARATORS improve current flow for faster starts.



