



NATIONWIDE BATTERY



DL+ PB 60

• LiFePO4 11 YEARS OF WARRANTY

- Voltage: 12V
- Reserve Capacity: 60Ah
- Energy [Wh]: 720
- Active BMS Protection
- Weight: 27 lbs (12.2 kg)
- Length: 11.6 in (295 mm)
- Width: 12.1 in (307 mm)
- Height: 12.8 in (325 mm)
- M8
- Operating Temperature: -20F to +150F
- **Battery Charger included**



Designed as a waterproof and submersible mobile power station for use in extreme environments, the Powerbox 60 is a fully field maintainable battery built to power many passions. Jump start a car or boat engine with over 1,000 cold cranking amps (CCA) of engine starting power. Power your devices and smaller appliances with 60 amp hours (720 Watt-hours) of deep cycle Dakota Lithium energy. Efficiently charge phones, laptops, camera equipment, TVs, monitors, portable fridges, medical devices, power tools, and more via the 2 AC wall plugs or the 6 USB ports. Connect jumper cables to the automotive grade battery posts to access up to 1,000 CCA of engine starting power or use the waterproof binder posts to run high amp applications like 12V trolling motors, electric coolers, or graphs & fish finders. All in one waterproof lithium battery so light that it floats.

200%

TWICE THE POWER OF TRADITIONAL BATTERIES

1/2

ONE HALF THE WEIGHT

5X

CHARGES UP TO 5X FASTER

8X

LASTS 8X LONG

100%

SAFE & RELIABLE



MODEL DL+ PB 60
 VOLTAGE 12V
 CAPACITY 60Ah
 BATTERY TYPE Dual Purpose Lithium Iron Phosphate
 CYCLE LIFE > 5,000 CYCLE @ 80% DOD
 INTELLIGENCE Active BMS Protection
 CERTIFICATION UN38 / UL1642 / IEC62133

12V

PRODUCT + PHYSICAL SPECIFICATIONS

BCI Group Size	Type	Voltage	Cell(s)	Terminal Type ^g	Dimensions ^e Inches (mm)			Weight Lbs. (kg)
					Length	Width	Height ^f	
24, 78, 51R	DL+ PB 60	12		M8	11.6 (295)	12.1 (307)	12.8 (325)	27 (12.2)

ELECTRICAL SPECIFICATIONS

Capacity ^A Minutes		Energy (Wh)			Short Circuit Current (amps)
@ 25 Amps	5-Hr	10-Hr	20-Hr	20-Hr	
-	60	60	60	720	

CHARGING INSTRUCTIONS

Charger Settings	
Recommended Charging Voltage	14.4V
Maximum Charging Voltage	15V
Maximum Charging Current @ Temperature	
> 32F (0C)	30
14F to 32 F (-10C TO 0C)	N/R
-4 F to 14 f (-20C to -10C)	N/R



CHARGING INSTRUCTIONS

80A max, 14.4V recommended, 15V max. Avoid charging below 32F

CHARGER INCLUDED

Free 12V 10A LiFePO4 charger included

OPERATIONAL DATA

Optimal Operating Temperature	Recommended Storage Temperature
-20°F to 150°F (-6°C to 49°C) At temperatures below 32°F (0°C) Charging Current Reduced	-20F to 120F (-6C to 49C)

Electrical Features	
Continuous Discharge Current	100Amps
Pulse Discharge Current @ 77°F (25°C)	750
Communication	N/A
BMS Protections	Cell balancing, low/high voltage cutoff, short circuit, high temperature
BMS Functions	Cell Balancing
Safety Systems	BMS
Series Connections	
Parallel Connections	
Discharge Voltage Cutoff	9.0V
Maximum Discharge Voltage	11.0V
Data Logging	
Other Features	
Environmental Protection	
Shipping Classification	
Case Flame Rating	
CCA	1000





HALF THE WEIGHT. TWICE THE POWER

All Dakota Lithium batteries are engineered with Lithium Iron Phosphate technology (LiFePO₄) providing long lasting performance in the harshest environments. Allowing you to go further, last longer, and play harder.

11 YEAR WARRANTY

Dakota Lithium offers a best in class 11 year pro-rated warranty on all of our batteries.

AMERICAN INNOVATION & USA BASED SUPPORT

SAFETY

Dakota Lithium has engineered the safest lithium battery technology on the market today - a battery that is safer than the one in your cellphone, camera, or laptop. Here are a few examples of how we manage safety here at Dakota Lithium:

SAFETY BATTERY MANAGEMENT SYSTEM (BMS) - Ensures safety and long battery lifespan All Dakota Lithium batteries include an active BMS protection circuit that handles cell balancing, low voltage cutoff, high voltage cutoff, short circuit protection and temperature protection for increased performance and longer life. Safety measures provided by the BMS prevent overheating. All Dakota Lithium batteries have a BMS that can support linking batteries in series or parallel.

LITHIUM IRON PHOSPHATE - LiFePO₄ Different Li-ion batteries use different chemistries. Dakota Lithium exclusively engineers our batteries using lithium iron phosphate or LiFePO₄ for short. Lithium Iron Phosphate batteries are the safest lithium battery chemistry. Unlike the cell phone battery in your pocket, or the laptop battery on your desk, the structural stability of LiFePO₄ results in significantly less heat generation compared to other lithium chemistries.

NO THERMAL RUNAWAY - Dakota Lithium cells do not produce oxygen The main cause of fire or explosion of a lithium ion battery is due to the cells being compromised or ruptured, which causes thermal runaway. Without proper management, thermal runaway may result in fire. Dakota Lithium LiFePO₄ is extremely stable and does not produce the oxygen needed to aid thermal runaway and unlike other lithium battery chemistries will not result in a catastrophic meltdown.

100% COBALT FREE - No rare earth elements NCM and other lithium ion chemistries that contain rare earth elements such as Colton or Cobalt produce oxygen and toxic fumes when ruptured, leading to fire. Dakota Lithium does not contain rare earth elements, and does not produce oxygen or is prone to fire.

CERTIFICATIONS - Tested and certified for safety and reliability Dakota Lithium batteries meet U.N. 38.3 standards and built from grade A cells. Dakota Lithium's cells are UL1642 certified and have been tested per IEC62133 standards. UN Manual of Tests and Criteria certified, and meets all US & International regulations for air, ground, marine, and train transport. Dakota Lithium is ISO Certified per 9001:2015 standards, and select models are produced in ISO 14001 certified facilities. IEC62133 certifications and additional laboratory services are available as required by our OEM clients.

INSTALLATION & CARE - Treat your batteries right When proper installation and battery care is followed, your LiFePO₄ battery will be safe and reliable for many years. This includes making sure all connections are tight and proper wiring sizes are used, **compatible chargers** and charging components are used, and the batteries are used for purposes that they are designed for.