MADE IN U. S. A.

NATIONWIDE BATTERY

MARINE | GOLF | INDUSTRIAL | AUTO | SPECIAL APPLICATIONS | SOLAR

ODYSSEY THE EXTREME BATTERY

POWERSPORT SERIES
ODS-AGM16CL

EXTREME POWER AND ENDURANCE

- **MAINTENANCE FREE – AGM VALVE REGULATED**
  - BCI Group N/A, 12V
  - CCA 200 / MCA 340 / PHCA 530
  - Reserve Capacity [min]: 27@25 A
  - Reserve Capacity [Ah@20hr rate]: 18
  - Weight: 13.20 lbs.
  - Length- 6.70 in (170.20 mm)
  - Width- 3.90 in (99.10 mm)
  - Height- 6.95 in (176.65 mm)
  - Type M6 Receptacles Positive Terminal on Right

ODYSSEY Powersport Series Battery Model ODS-AGM16CL
FORMER PC325

Powersport vehicles need a powerful battery that's built to take the constant pounding that comes with the territory, whether it's is on land, sea, or snow.

The ODYSSEY battery can handle it. Featuring rugged construction and packed tightly with pure lead plates, the non-spillable AGM design ODYSSEY battery protects against the shock and vibration that can quickly destroy other batteries. And the pure lead plates mean more power-twice the overall power and three times the life of conventional batteries-up to 400 cycles at 80% depth of discharge!

EnerSys Power/Full Solutions

DESIGN ADVANTAGES

1

Robust Intercell Connections
Are cast to the plates and bonded to resist vibration and eliminate internal sparking

2

99% Pure Lead Plates
Are extremely thin, so more of them fit in the battery. More plates = more power

3

Upgraded Brass Terminals
Ensure secure, corrosion free cable connections (some models may have plated brass terminals)

4

Compressed AGM Plate Separators
deliver extreme vibration resistance and prevent spills, even when battery is installed on its side

ODYSSEY BATTERIES VS SPIRAL WOUND DESIGN

EnerSys Power/Full Solutions

NATIONWIDE BATTERY

ODYSSEY

THE EXTREME BATTERY

	ODYSSEY EXTREME BATTERIES	CONVENTIONAL BATTERIES
DESIGN LIFE	8-12 YEARS (Float) @ 77F (25C)	5 years
SERVICE LIFE	3 to 10 years	1 to 5 years
ELECTROLYTE	Drycell (“starved electrolyte”) no external leakage or corrosion	Most are acid flooded (causing acid burns and spills); some wet sealed or gelled
STORAGE LIFE	2 years before needing charge @ 77F (25C)	6-12 weeks before needing charge
SHIPPING	Air transportable up to BCI31;US Department of Transportation classified non spillable (less expensive)	Ground Transport; classified as hazardous resulting in more expensive (flooded batteries)
END OF LIFE	Battery Slowly loses power at end of life; no catastrophic failure	Immediate and catastrophic loss of power (can leave you stranded)

WHY USE ODYSSEY BATTERIES

Better warranty
Up to 4-year limited full replacement warranty — not pro rata.

Longer service life
3-10 years of service life to save you time, money, and aggravation

Longer cycle life
70% longer cycle life than conventional deep cycle batteries — high stable voltage for longer periods of time.

Longer shelf life
Can be stored on open circuit (nothing connected to the terminals) without recharging for up to 2 years or 12.00V, whichever occurs first.

Faster recharge
The highest recharge efficiency of any sealed lead battery on the market — capable of 100% recharge in 4-6 hours.

Mounting flexibility
Non-spillable design — can be mounted on any side in any position except inverted.

Vibration resistance
Design protects against high impact shock and mechanical vibration — a common cause of premature battery failure.

Extreme temperature tolerant
Operating temperatures from -40°C (-40°F) to 45°C (113ºF), for models without a metal jacket, and from -40ºC (-40ºF) to 80ºC (176ºF) for models with a metal jacket.

Totally maintenance free
No need to add water, ever! Drycell design with resealable venting system.

Improved safety
US Department of Transportation classified as a ‘non-spillable’ battery. No acid spills, no escaping gases.